



GENERAL SPECIFICATIONS *

• Overall Length (L.O.A)	9,53 m	31'3"
• Hull length	8,99 m	29'6"
• L.W.L.	8,65 m	28'5"
• Hull Beam (max)	2,99 m	9'10"
• Deep draft (Cast iron)	1,88 m	6'2"
• Deep ballast weight	973 kg	2,144 lbs
• Shallow draft (Cast iron)	1,30 m	4'3"
• Shallow ballast weight	1 150 kg	2,535 lbs
• Lifting keel version draft (Ballast melting)	0,95 - 2,33 m	3'1" - 7'8"
• Lifting keel version ballast weight	1 300 kg	2,865 lbs
• Air draft	13,66 m	44'10"
• Light displacement	3 995 kg	8,805 lbs
• Fuel tank capacity (standard)	130 L	34 US Gal
• Fresh water capacity (standard)	160 L	42 US Gal
• Engine power (standard)	15 HP	15 HP
• Engine power (Option)	21 HP	21 HP

ARCHITECTS / DESIGNERS

- Naval Architect: Pascal Conq
- Interior design: Nauta Design

EC CERTIFICATION *

- Category B - 6 people
- Category C - 8 people
- Category D - 10 people

STANDARD SAILS DIMENSIONS *

• Square top mainsail	23,80 m ²	256 sq/ft
• Furling mainsail	18,80 m ²	202 sq/ft
• Self-tacking jib	15,70 m ²	169 sq/ft
• Genoa (105 %)	22,10 m ²	238 sq/ft
• Code 0	34,80 m ²	374 sq/ft
• Asymmetrical spinnaker	70,00 m ²	753 sq/ft
• I	11,02 m	36'2"
• J	3,87 m	12'8"
• P	10,81 m	35'6"
• E	3,27 m	10'9"

* Provisional specifications, boat in process of certification.



BENETEAU

Oceanis 30.1

General Equipment list (Provisional) - North America

STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to CE certification
- Monolithic hull in polyester
- Monolithic contact structural counter mold (Fabric - resin) bonded to the hull
- Fiberglass and foam sandwich contact deck - coated with "diamond point" type non-slip
- Hull deck joint glued and screwed
- Cast iron keel fixed with bolts and stainless steel backing plates
- Twin rudders affixed with stainless steel stock
- White hull - Grey metal hull decoration
- 2 Hull portlights

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 anodized aluminum on deck stepped, 1 Set of spreaders
- Anodized aluminum boom
- Discontinuous stainless steel standing rigging (Forestay- Side shrouds)
- No backstay
- 1 Standard forestay
- 1 Rigid boom vang
- 1 Jib furler with drum on deck
- 2 Mainsail sheet padeyes
- 1 Self-tacking jib sheet track with traveller attached to the deck
- Mainsheet and halyards led to the coachroof (except boom topping lift - foot)
- Complete running rigging:
 - 1 Main halyard
 - 1 Jib halyard with cleat and mast cleat
 - 1 Boom topping lift with cleat on mast
 - 1 Mainsail outhaul
 - 1 Mainsail sheet (Bridle led to the coachroof)
 - 2 Jib sheets
 - 2 Reefing lines
- 5 Clutches (to port)

WINCHES

- 1 Self tailing winch (H20.1 STA) on the coachroof (portside)
- 1 Aluminum Harken B8 winch handle
- 1 Winch handle holder

SAILS

- Self-tacking jib on a furler Dacron with UV Natural protection, horizontal section
- Classic square topped mainsail (900 mm), semi battened with slides, Natural UV protection, horizontal section
- Lazy Jack System and Lazy bag in Natural color

MOORING - ANCHORING GEAR

- Self-draining chain locker - Clench bolt - Hatch cover
- Single roller stainless steel bow fitting with offset roller
- 6 Aluminum mooring cleats - Stainless steel chafing plate

SAFETY ON DECK

- Stainless steel pulpit 2 sections
- 2 Stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- Welded ring on pushpit for flag
- Double life lines and stainless steel stanchions
- Emergency ladder on pushpit

COCKPIT

- Self-bailing cockpit in polyester
- 1 Starboard locker (Sail locker, Liferaft storage)
- 1 Single gas compartment on the port side
- 1 Gas compartment under port helmsman seat
- Natural solid wood slatted cockpit benches
- Stainless steel tiller with telescopic tiller extension
- 1 Steering compass on the coachroof (starboard)
- Engine throttle and control panel on starboard
- 2 Deck accesses for emergency tiller
- 1 Emergency tiller
- PMMA companionway hatch and door with guillotine door and height-adjustable coaming

SWIM PLATFORM / STERN DECK (in trim level)

- Full-opening tilting transom (1,90 m x 0,35 m / 6'3" x 1'2")
- Manually controled
- Natural solid wood sole on swim platform

INTERIOR

- Alpi white oak wood interior
- Brown oak laminated floors
- Upholstery padding: Taupe
- Interior cushions in cloth: Néo 05

COMPANIONWAY

Headroom: 1,89 m / 6'2"

- GRP salon companionway 3 steps are coated with non-slip surface
- 2 Stainless steel handrails covered with anthracite leather

SALON

Headroom: 1,90 - 1,85 m / 6'3" - 6'1"

- 2 Lengthways salon bench seats
- Salon table with 2 folding seats, bottle rack and central storage
- Storage under bench seats
- Indirect LED lighting above the benches
- 2 LED ceiling lights
- 1 USB socket on the electrical panel
- 2 Panoramic roof windows
- 2 Hull portlights
- 1 Opening deck hatch with ventilator, T44

GALLEY - PORTSIDE

Headroom: 1,85 m / 6'1"

- L-shaped kitchen
- Counter top in compact Clay with painted wooden fiddles
- 1 rectangular stainless steel sink (350 mm x 320 mm / 1'2" x 1'1")
- 1 Faucet with hot/cold water under pressure
- 1 Gas stove 2 burners - Stainless steel oven on gimbal - Stainless steel protection handrail
- 1 Cool box 75 L / 20 US Gal/top opening (refrigeration unit included in trim level)
- Cupboard - Storage and lockers
- 1 Double trash can: 2 x 15 L / 4 US Gal
- 2 LED ceiling lights
- 1 Opening portlight with curtains in the coachroof side window

CHART TABLE - STARBOARD (OPTIONAL EXTRA)

- Chart table with folding tray against the starboard bulkhead with shelves fitted with fiddles in the upper part
- Electrical panel nearby
- 1 Swivelling LED reading light

FORWARD CABIN

Headroom: 1,85 m / 6'1"

- Double access door
- Double bed (2,00 m x 1,90 - 0,50 m / 6'7" x 6'3" - 1'8")
- Mattress in 2 parts (thickness: 10 cm)
- 2 Cupboard units: 1 Port hanging locker - Starboard shelves - Open shelves above
- Open top shelves 2 sides of the bed
- 2 LED reading lights
- Indirect LED lighting under shelving along the hull
- 1 Opening hatch with air vent, T44

AFT CABIN

Headroom: 1,89 m / 6'2"

- Double bed (2,00 - 1,85 m x 1,60 - 1,35 m / 6'7" - 6'1" x 5'3" - 4'5")
- 1 Cupboard with shelves - Open shelves above
- Open high shelving along the hull
- 2 LED reading lights
- Indirect LED lighting under shelving along the hull
- 2 Opening portholes on the cockpit seat back and on the coachroof

OWNER'S HEAD - STARBOARD

Headroom: 1,88 m / 6'2"

- Access through salon
- Counter top with built-in basin
- 1 Mixing tap hot/cold water
- 1 Hot and cold cockpit shower
- 1 Manual marine toilet with 80 L / 21 US Gal rigid reserve
- 1 Mirror
- Toilet accessories
- Cupboard, storage, shelving
- 1 LED ceiling light
- Indirect LED lighting under shelving along the hull
- 1 Opening portlight with curtains in the coachroof side window
- 1 Shower curtain

ENGINE

- Engine Yanmar Diesel (Propeller shaft):
 - 15 HP/15 *HP* (standard)
 - 21 HP/21 *HP* (Option)
- Engine control - Control panel in cockpit, starboard
- Engine compartment: Soundproofing foam - Ventilation: 2 air intakes and 1 forced air outlets
- 1 Alternator (12 V / 125 Amp)
- 1 Rotomolded diesel tank 130 L / 34 *US Gal* (under the sail locker) - Gauge on electrical panel - 1 Tank filling access
- Filters: Sea water - Diesel - Water separator
- Stainless steel shaft line
- Fixed two-blade propeller
- 1 Engine access through companionway (opening with 2 gas pistons)
- 2 Access to side engine: Head & Aft cabin

ELECTRICITY

- 12 V Circuit
- 1 Service battery (80 Amperes) - 1 Engine battery (50 Amperes)
- 1 Load balancer
- 12 V Electrical panel (Fuses - Voltmeter - 1 Fuel gauge)
- 1 USB port dual port, in the salon
- LED lighting: Overhead lights & Indirect light - Cabin and chart table reading lights
- LED navigation lights: 1 Masthead light - 1 Steaming light for motoring - 1 Mooring light on masthead

PLUMBING

- 1 Rotomolded freshwater tank 160 L / 42 *US Gal*, under berth in forward cabin
- Manual gauge on the tank
- Tank filling access, stainless steel
- Waterpressure system - Expansion tank - Inline filter
- 1 25 L / 7 *US Gal* Electric water heater (engine use)
- 1 80 L / 21 *US Gal* Rigid holding tank
- Electric shower drain pump
- 1 Electric bilge pump - 1 Manual bilge pump

GAS

- 1 Gas cylinder locker - starboard aft cockpit (25 cm x 27 cm x 40 cm / 10" x 11" x 15")
- Regulator and solenoid
- Gas leak detector

TRIM LEVEL & PACKS

TRIM LEVEL

CONFORT TRIM PACKAGE

- Natural solid wood decked aft platform with manual opening, 1 Retractable stainless steel swimming ladder
- Polyester drop-leaf cockpit table
- 2 Halyard bags
- Blinds / mosquito nets on 2 deck hatches, blackout curtains on hull portholes, curtains on coaming windows, curtains and mosquito nets on opening portholes of the aft cabin
- Galley: 12 V Refrigeration unit in icebox
- Hifi: Fusion player + Interior speakers & Waterproof exterior speakers
- Full 12/115 V system (1 Internal socket on the electrical panel, 1 USB socket in the cabins, 25 Amp battery charger, 1 80 Amp extra battery, Shore power socket)

ELECTRONICS PACKS: B&G

PACK COASTAL

- 1 Triton 2 Graphic display, to starboard from the companionway
- Sensor (Log, Speedometer, Temperature)
- Wind Sensor (Windvane, Anemometer)
- Windex Windvane

PACK OFFSHORE

- Chart table: B&G V60 VHF, AIS receiver function
- Multifunction touchscreen Zeus³ 7" wide wireless (GPS, Chart plotter, Card reader - Navionics Silver cartography included) to starboard from the companionway

RIGGING PACKS

	PACK DOWNWIND	PACK UPWIND	PACK DOWNWIND + UPWIND
• 2 Genoa winches (H35.2 STA)	■	■	■
• 1 Self tailing maneuvering winch (H20.1 STA) on the roof (starboard) + blockers	■		■
• Symmetrical spinnaker rigging / Code 0	■		■
• Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker use)	■		■
• Genoa sheet tracks on side decks		■	■
• Furling Dacron genoa (to replace the standard self-tacking jib)		■	■

OPTIONS

NAVIGATION ELECTRONICS: B&G

- B&G NAC3 Autopilot + Control WR10 Smart Wifi

RIGGING - SAILS

- Anodized mast furling system with Dacron mainsail
- Code 0 with Mylar Taffetas furler

INTERIOR EQUIPMENT

- Interior upholstery: PVC Marlin Weiss
- Chart table furniture in the starboard salon
- Wood companionway steps
- Fresh sea water foot pump
- Yacht Case - Tableware
- Diesel heater "air pulse"
- 12 V / 115 V inverter (700 VA)

HULL - DECK - COCKPIT

- Ballasted boat version
- Fixed keel shallow draft version
- Pearl Grey hull
- Double steering wheel version
- Cockpit table cover
- Solid wood decking on cockpit sole
- Steering wheels covers (White PVC)
- Silver Coachroof sprayhood
- Silver Cockpit bimini
- Dolce 51 Cockpit cushions
- 3 folding blades propeller (with 21 CV engine only)
- Rope cutter
- 700 W Electric windlass - Remote control
- Shore freshwater supply
- Cockpit shower (hot/cold water)
- Outboard engine bracket (Pushpit)
- Complete mooring/anchoring kit
- Aft transom protection